

2002 bicycle specifications



P R E C I S I O N C Y C L I N G

MADELEINE / ISIS / SYMMETRY / CLASSIC / TRIXIE / SUSAN B. / AMELIA / TITANIA



col de la *Madeleine*

For the touring cyclist who wants the very best, uniquely equipped with straight bars and wider tires

Premier Reynolds 520 cromoly steel tubing

Relaxed frame geometry (same as the Terry Classic)

Shimano Ultegra and Deore XT level components

New lightweight wheels

Brake clearance for fenders

Extra-wide range of gearing

Front and rear rack braze-ons

Color: Beaujolais

Weight: 20 lbs.

Suggested Retail: \$2,000

Isis

New premier Reynolds 520 tubing

Shimano Ultegra level components

New lightweight wheels (not shown)

Color: Blue Lagoon

Weight: 20 lbs

Suggested Retail: \$2,000

MADELEINE COMPONENTS

Frame	Reynolds 853 double-buttet CrMo tubing, TIG welded
Fork	Reynolds 520 double-buttet CrMo tubing, TIG welded
Headset	Shimano Ultegra 1", threaded steerer, English threads, alloy silver
Crankset	Shimano Ultegra Triple, 165mm (16"; 17.5"; 19"), 170mm (20.5"; 22"; 23") 30/42/52 chainrings
Bottom Bracket	Shimano Ultegra cartridge
Front Derailleur	Shimano Road triple; 28.6 clamp-on; capacity: 22 teeth
Rear Derailleur	Shimano Deore XT, capacity: 43 teeth; largest sprocket: 34 teeth
Shift/Brake Levers	Shimano Deore XT Rapidfire: 9-speed
Cassette	Shimano Deore XT, steel, 11 x 32, 9-speed
Chain	KMC Z-9900, 1/2" x 3/32"
Brakes	New Shimano dual pivot sidepull: 57 mm reach
Hubs	Velocity sealed bearing, 32 hole, black anodized, quick release
Rims	Velocity Aerohead, black anodized; machined sidewalls, presta valve
Tires	Panaracer Tecnova 28-520, 24" x 1 1/8" front (16"; 17.5"; 19") Panaracer Pasele TG Compe 32-622, 700c x 32 rear (all sizes) and front (20.5"; 22"; 23"), kevlar belt
Seatpost	Kalloy carbon fiber, 250mm
Saddle	Terry Butterfly black leather, titanium rails
Stem	Terry Hi-Rise Combo; 65mm; 210 x 22.2 shank, 30° rise; 2-bolt version
Handlebar	Kalloy alloy, silver, 560mm, 25.4 clamp
Pedals	None supplied
Reflectors	Full CPSC standard
Braze-ons	Front and rear rack; 2 water bottle bosses; derailleur cable guides; pump peg
Manual	Terry 2002 Owner's Manual

ISIS COMPONENTS

Frame	Reynolds 853 double-buttet CrMo tubing, TIG welded
Fork	Reynolds 520 double-buttet CrMo tubing, TIG welded
Headset	Shimano Ultegra 1", threaded steerer, English threads, alloy silver
Crankset	Shimano Ultegra Triple, 165mm (16"; 17.5"; 19"), 170mm (20"; 21.5"; 23") 30/42/52 chainrings
Bottom Bracket	Shimano Ultegra cartridge
Front Derailleur	Shimano Ultegra triple; 28.6 clamp-on; capacity: 22 teeth
Rear Derailleur	Shimano Ultegra; capacity: 37 teeth; largest sprocket: 27 teeth
Shift/Brake Levers	Shimano Ultegra STI levers; 9-speed indexed
Cassette	Shimano Ultegra, steel, 12 x 27, 9-speed
Chain	KMC Z-9900, 1/2" x 3/32"
Brakes	Shimano Ultegra Super SLR dual pivot sidepull; 49mm reach
Hubs	Velocity sealed bearing, 24 hole (front) 28 hole (rear), black, quick release
Rims	Velocity Aerohead, black anodized, machined sidewalls, presta valve
Tires	Panaracer Tecnova 25-520, 24" x 1" front (16"; 17.5"; 19") Panaracer Stradius Sport 26-622, 700c rear (16"; 17.5"; 19"); front & rear (23") Terry 28-571, 650c x 28 front & rear (20"; 21.5")
Seatpost	Kalloy carbon fiber, 250mm
Saddle	Terry Butterfly, black leather, titanium rails
Stem	Terry T-Stem road, 65mm, 210 x 22.2 shank, 0° rise, 2-bolt version
Handlebar	Terry T-Bar 26.0, patented design
Handlebar Tape	Co-Union, black/blue
Pedals	None supplied
Reflectors	Full CPSC standard
Braze-ons	Rear rack braze-ons, 2 sets water bottle bosses, derailleur cable guides; pump peg
Manual	Terry 2002 Owner's Manual

Terry Precision Cycling • 1657 East Park Drive • Macedon NY 14502

315-986-2103 (customer service) • 315-986-2104 (fax) • 800-289-8379 (order desk) • www.terrybicycles.com/IBD/ibd.html



Symmetry

Upgraded lightweight Reynolds cromoly steel tubing

Best fitting, best value road bike made specifically for women

Shimano Tiagra level components

Triple crankset + 9-speed cassette

Colos: Pearl or Heron Blue

Weight: 22 lbs

Suggested Retail: \$1,150

SYMMETRY COMPONENTS

Frame	Reynolds 631 double-buttet CrMo tubing, TIG welded
Fork	Reynolds 520 double-buttet CrMo tubing, TIG welded
Headset	YST 1", threaded steerer
Crankset	Shimano Tiagra Triple, 165mm (16", 17.5", 19"); 170mm (20", 21.5", 23") 30/42/52 chainrings
Bottom Bracket	Shimano Tiagra cartridge
Front Derailleur	Shimano Tiagra triple; 28.6 clamp-on; capacity: 22 teeth
Rear Derailleur	Shimano Tiagra; capacity: 37 teeth; largest sprocket: 27 teeth
Shift/Brake Levers	Shimano Tiagra STI levers; 9-speed indexed
Cassette	Shimano Tiagra, steel, 12 x 25, 9-speed
Chain	KMC Z-9000, 1/2" x 3/32"
Brakes	Shimano Tiagra Super SLR dual pivot sidepull; 49mm reach
Hubs	Shimano Sora 32 hole; quick release
Rims	Velocity Aerohead, silver, presta valve
Tires	Panaracer Tecnova 25-520, 24" x 1" front (16", 17.5", 19") Panaracer Stradius Sport 26-622, 700c rear (16", 17.5", 19"); front & rear (23") Terry 28-571, 650c x 28 front & rear (20", 21.5")
Seatpost	Kalloy Uno, alloy, 250mm, silver
Saddle	Terry Butterfly CrMo; black vinyl, steel rails (not shown)
Stem	Terry T-Stem road; 65mm; 210 x 22.2 shank; 0° rise; 2-bolt version
Handlebar	Terry T-Bar 26.0, patented design
Handlebar Tape	Co-Union black/white or white/blue
Pedals	Terry combination pedal system
Reflectors	Full CPSC standard
Braze-ons	Rear rack braze-ons; 2 sets water bottle bosses; derailleur cable guides; pump peg
Manual	Terry 2002 Owner's Manual

Classic

A road bike, uniquely equipped with straight bars and wider tires

Extra-wide range of gearing

New brake clearance for fenders

Terry high rise stem for more upright positions

Front and rear rack braze-ons

Colors: Hi Ho Silver or Lavender Mist

Weight: 22 lbs

Suggested Retail: \$1,150

CLASSIC COMPONENTS

Frame	Reynolds 631 double-buttet CrMo tubing, TIG welded
Fork	Reynolds 520 double-buttet CrMo tubing, TIG welded
Headset	YST 1", threaded steerer
Crankset	Shimano Tiagra triple, 165mm (16", 17.5", 19"); 170mm (20", 22", 23")
Bottom Bracket	Shimano Tiagra cartridge
Front Derailleur	Shimano Road triple, 28.6 clamp-on; capacity: 22 teeth
Rear Derailleur	Shimano Deore; capacity: 43 teeth; largest sprocket: 34 teeth
Shift/Brake Levers	Shimano Deore Rapidfire; 9-speed
Cassette	Shimano Deore; 11 x 32; 9-speed
Chain	KMC Z-9000, 1/2" x 3/32"
Brakes	New Shimano dual pivot sidepull; 57mm reach
Hubs	Shimano Sora 32 hole; quick release
Rims	Velocity Aerohead, silver presta valve
Tires	Panaracer Tecnova 28-520, 24" x 1 1/8" front (16", 17.5", 19") Panaracer Pasela TG Compe 32-622, 700c x 32 rear (all sizes) and front (20.5", 22", 23"), kevlar belt
Seatpost	Kalloy Uno, alloy, 250mm, black
Saddle	Terry Butterfly CrMo, black vinyl, steel rails (not shown)
Stem	Terry Hi-Rise Combo; 65mm; 210 x 22.2 shank, 30° rise; 2-bolt version
Handlebar	Kalloy alloy, black, 560mm, 25.4 clamp
Pedals	Terry combination pedal system (not shown)
Reflectors	Full CPSC standard
Braze-ons	Front and rear rack; 2 water bottle bosses; derailleur cable guides; pump peg
Manual	Terry 2002 Owner's Manual



Amelia

The best fitting mountain bike made for women

Front suspension and suspension seatpost

Shimano Alivio level components

Triple crankset + 8-speed cassette

Color: Thunder Gray

Weight: 31 lbs

Suggested Retail: \$550

AMELIA COMPONENTS

Frame	Double-butted CrMo tubing, TIG welded
Fork	Terry RST elastomer suspension
Headset	Tange 1 1/8"; threadless steerer
Crankset	Shimano Alivio triple, 170mm 22/32/42 chainrings
Bottom Bracket	Shimano LP27 cartridge
Front Derailleur	Shimano Alivio triple, 28.6 clamp-on; capacity: 20 teeth
Rear Derailleur	Shimano Alivio; capacity: 39 teeth; largest sprocket: 30 teeth
Shift/Brake Levers	Shimano Alivio Rapidfire Plus for V-brake; 8-speed indexed
Cassette	Shimano Alivio, steel; 11 x 30 8-speed
Chain	KMC 1/2" x 3/32"
Brakes	Shimano Alivio V-Brake
Hubs	Shimano Alivio, 32 hole; quick release
Rims	Velocity Aeroheat AT alloy, black anodized, machined sidewalls; presta valve
Tires	Vee Rubber VRB-165 24" x 1.90" (11"; 14"); 26" x 1.95" (16"; 18"; 20")
Seatpost	Kalloy alloy, 300mm, quick release
Saddle	Terry Mrs. Cox; black vinyl, steel rails
Stem	HL Stem, 120mm, 40° rise, 3 spacers
Handlebar	HL alloy, black, 560mm, 25.4 clamp
Bar Ends	JD alloy, black
Pedals	VP steel, black with toe clips (not shown)
Reflectors	Full CPSC standard
Braze-ons	Rear rack braze-ons; 2 sets water bottle bosses; derailleur cable guides
Manual	Terry 2002 Owner's Manual



Susan B.

A hybrid bicycle specifically made for women

Shimano Acera level components

Triple crankset + 7-speed cassette

Color: Purple Passion

Weight: 24 lbs

Suggested Retail: \$450

SUSAN B. COMPONENTS

Frame & Fork	Double-butted CrMo tubing, TIG welded
Headset	YST 1 1/8"; threaded steerer
Crankset	Shimano Acera triple, 170mm, 22/32/42 chainrings
Bottom Bracket	Shimano LP27 Cartridge
Front Derailleur	Shimano Acera triple, 28.6 clamp-on; capacity: 20 teeth
Rear Derailleur	Shimano Acera; capacity: 45 teeth; largest sprocket: 34 teeth
Shift/Brake Levers	Shimano Acera Rapidfire Plus for V-brake; 7-speed indexed
Cassette	Shimano Acera; steel; 11 x 28, 7-speed
Chain	KMC IG31
Brakes	Shimano Acera V-brake
Hubs	Shimano Acera; 32 hole; quick release
Rims	Velocity Aeroheat AT alloy, silver; presta valve
Tires	Vee Rubber VRB-182 24" x 1.25" (11"; 14"); 26" x 1.25" (16"; 18"; 20")
Seatpost	Kalloy alloy, silver, quick release
Saddle	Terry Women's Liberator Cité; black vinyl, steel rails
Stem	Terry Hi-ATB; 65 x 210mm, 15° rise
Handlebar	HL alloy silver, 580mm, 1" rise, 25.4 clamp
Bar Ends	JD Alloy, silver
Pedals	VP steel, black with toe clips (not shown)
Reflectors	Full CPSC standard
Braze-ons	Rear rack braze-ons; 2 sets water bottle bosses; derailleur cable guides
Manual	Terry 2002 Owner's Manual



Trixie

Custom women's sizing in a classic, mixte frame

Shimano 105/Deore LX level components

Triple crankset + 9-speed cassette

Front and rear rack braze-ons

Color: Aqua

Weight: 23 lbs

Suggested Retail: \$1,200

TRIXIE COMPONENTS

Frame & Fork	Double-buttressed CrMo tubing, TIG welded, step-through frame
Headset	Shimano 105 1" sealed, threaded steerer
Crankset	Shimano 105 triple, 165mm (16", 17.5", 19"); 170mm (20", 22") 30/42/52 chainrings
Bottom Bracket	Shimano 105 cartridge
Front Derailleur	Shimano Deore LX, 28.6 clamp-on; capacity: 22 teeth
Rear Derailleur	Shimano Deore LX; capacity: 45 teeth; largest sprocket: 34 teeth
Shift/Brake Levers	Shimano Deore LX Rapidfire
Cassette	Shimano Deore LX; steel, 11 x 32, 9 speed
Chain	Shimano 1/2" x 3/32"
Brakes	Shimano Deore LX V-brake
Hubs	Shimano 105; quick release
Rims	Velocity Aerohead, silver; 32 hole; presta valve
Tires	Panaracer Touring 28-520, 24" front (16", 17.5", 19") Panaracer Pasela 32-622, 700c x 32c with Kevlar® bead rear tire (all sizes) and front tire (20.5", 22")
Seatpost	Kalloy alloy, silver, quick release
Saddle	Terry Mrs. Cox; black vinyl, steel rails
Stem	Terry Hi Rise Combo stem road; 65 x 210mm, 30° rise
Handlebar	HL alloy, silver, 560mm, 25.4 clamp, 1" rise
Pedals	Terry combination pedal system (not shown)
Reflectors	Full CPSC standard
Braze-ons	Front and rear rack braze-ons; water bottle bosses; derailleur cable guides
Manual	Terry 2002 Owner's Manual



Titania

Titanium road frame and CroMoly steel fork, made by hand in the USA

Sold as frame and fork only—you build up the bike to your specifications through your bike shop

Same women's-specific frame geometries as the Terry Isis, or have one custom-made just for you

Extremely lightweight, responsive frame

Custom decals and painted fork

■ Inches ■ Centimeters

	Size	Standover	Head Angle	Seat Angle	Top tube	Seat Tube	BB Height	Chainstay	Rake	Wheel Base
ISIS & SYMMETRY	16	26.7	72°	73°	18.9	16	10.3	16.7	1.9	37.8
	40.6	67.8			48.0	40.6	26.2	42.5	4.8	95.9
	17.5	28.2	72°	73°	19	17.5	10.3	16.7	1.9	38
	44.5	71.5			48.3	44.5	26.2	42.5	4.8	96.3
	19	29.6	72°	73°	19.3	19	10.3	16.7	1.9	38.2
	48.3	75.1			49.0	48.3	26.2	42.5	4.8	97
	20	30.3	72°	74°	20	20	10.5	16.9	2	39.1
	50.8	77			50.8	50.8	26.7	42.9	5.3	99.4
21.5	31.6	72°	73°	20.5	21.5	10.5	16.9	2.1	39.3	
54.6	80.3			52	54.6	26.7	42.9	5.2	99.7	
23	34.2	72°	73°	21	23	10.5	16.9	2.1	39.8	
58.4	86.8			53.3	58.4	26.7	42.9	5.2	101	
MADELEINE & CLASSIC	16	26.3	71.5°	73°	19.3	16	10.4	16.9	2	38.2
	40.6	66.8			49.1	40.6	26.5	42.9	5.1	97
	17.5	27.8	71.5°	73°	19.4	17.5	10.4	16.9	2	38.3
	44.5	70.5			49.3	44.5	26.5	42.9	5.1	97.3
	19	29.2	71.5°	73°	19.5	19	10.4	16.9	2	38.4
	48.3	74.2			49.5	48.3	26.5	42.9	5.1	97.6
	20.5	30.6	71°	73°	21.4	20.5	10.4	17	2.4	40.3
52.1	77.8			54.3	52.1	26.5	43.2	6.1	102.4	
22	32.1	71°	73°	21.4	22	10.4	17	2.4	40.4	
55.9	81.4			54.3	55.9	26.5	43.2	6.1	102.5	
23	33	71°	73°	21	23	10.4	17	2.4	40	
58.4	83.8			53.3	58.4	26.5	43.2	6.1	101.6	
TRIXIE	16	23.4	71.5°	73°	19.3	16	10.2	16.9	2	38.3
	40.6	59.5			48.9	40.6	26	42.9	5.1	97.2
	17.5	24.5	71.5°	73°	19.3	17.5	10.2	16.9	2	38.4
	44.5	62.1			49.1	44.5	26	42.9	5.1	97.5
	19	25.5	71.5°	73°	19.4	19	10.2	16.9	2	38.6
	48.3	64.8			49.3	48.3	26	42.9	5.1	97.8
20.5	26.4	71°	73°	21.4	20.5	10.4	17	2.4	40.5	
52.1	67.2			54.3	52.1	26.5	43.2	6.1	102.8	
22	27.5	71°	73°	21.4	22	10.4	17	2.4	40.5	
55.9	69.7			54.3	55.9	26.6	43.2	6.1	102.9	
SUSAN B.	11	24.1	69°	73°	19.9	11	11.5	16.7	1.8	39.7
	27.9	61.2			50.5	27.9	29.2	42.4	5.5	100.8
	14	25.9	69°	73°	20	14	11.5	16.7	1.8	39.8
	36.1	65.7			50.7	36.1	29.2	42.4	5.5	101.1
	16	28.3	71°	73°	20.9	16	11.5	16.7	2	40
	40.6	71.9			53.2	40.6	29.2	42.4	5.1	101.5
18	30.1	71°	73°	21	18	11.5	16.7	2	40.1	
45.7	76.5			53.4	45.7	29.2	42.4	5.1	101.8	
20	31.2	71°	73°	21.3	20	11.5	16.7	2	40.4	
50.8	79.3			54	50.8	29.2	42.4	5.1	102.5	
AMELIA	11	25.9	71°	73°	20.9	11	11.5	16.7	1.5	39.4
	27.9	65.8			53	27.9	29.2	42.4	3.8	100.2
	14	27.7	71°	73°	20.9	14	11.5	16.7	1.5	39.4
	36.1	70.4			53	36.1	29.2	42.4	3.8	100.2
	16	30	71°	73°	22.1	16	11.5	16.7	1.5	40.6
	40.6	76.2			56	40.6	29.2	42.4	3.8	103.2
18	31.4	71°	73°	22.3	18	11.5	16.7	1.5	40.9	
45.7	79.8			56.6	45.7	29.2	42.4	3.8	103.8	
20	32.5	71°	73°	22.5	20	11.5	16.7	1.5	41.1	
50.8	82.6			57.2	50.8	29.2	42.4	3.8	104.4	